

Technical Datasheet

GRAFFITI-REMOVER

Powerful graffiti remover

Description

GRAFFITI-REMOVER is a powerful graffiti removal agent, effective on spray paint, marker, etc. Suitable for use on a wide variety of surface types.

Fields of application

Used for graffiti removal from all common surfaces, including metal, glass, marble, stone, concrete, exposed masonry, etc. Suitable also for use on painted surfaces – tested first on an inconspicuous area.

Technical data

Color: transparent
Density: 1.03 kg/l

Directions for use

Soak a sponge in GRAFFITI-REMOVER and softly rub it over the surface wearing protective gloves. Repeat if necessary. Finally, rinse the surface with clean water.

Consumption depends on graffiti type and surface absorbency.

After cleaning, provided that the surface has completely dried, it is recommended to protect it with ISOMAT AG 80-2K, the special, transparent, polyurethane varnish for protecting surfaces from graffiti. ISOMAT AG 80-2K prevents graffiti paint from penetrating into the substrate and is not affected from the use of GRAFFITI-REMOVER. As a result, the surfaces are protected for longer.

Packaging

0.7 l containers.

Shelf life – Storage

36 months from production date if stored in original, sealed packaging, in areas protected from high temperatures (<+30°C).

Remarks

- In case GRAFFITI-REMOVER is to be used in interior applications, measures for proper ventilation have to be taken.
- Smoking and the use of flame during the application of the product should be avoided.
- Please consult the directions for safe use and precautions written on the packaging before use.

ISOMAT S.A.
BUILDING CHEMICALS, MORTARS & PAINTS
HEADQUARTERS – THESSALONIKI, GREECE
17th km Thessaloniki – Ag. Athanasios Road
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece
T +30 2310 576000
www.isomat.eu e-mail: support@isomat.eu