

JOINT SEALING TAPE

Sealing tape

Description

Special tape made of thermoplastic elastomer for waterproofing of joints in wet areas.

Fields of application

JOINT SEALING TAPE is used for waterproofing of joints in wet areas (bathrooms, kitchens, public showers, etc.). Suitable for indoor use on a variety of substrates such as concrete, cement screeds, gypsum panels, old layers of tiles, terrazzo, masonry, etc.

Technical data

Substrate:	Modified polyester knit fabric
Coating:	Thermoplastic elastomer, resistant to aging
Total Width:	12 cm
Coating Width:	7 cm
Thickness:	0.54 mm
Weight:	495 g/m ²
Temperature resistance:	-30°C - +90°C

Directions for use

1. Substrate

Substrate must be stable, clean and suitable for tiling.

2. Application

JOINT SEALING TAPE is adhered to the joints by using the waterproofing products ISOMAT SL-17, AQUAMAT-FLEX, or AQUAMAT-ELASTIC.

Apply the waterproofing slurry to the joint and while is still fresh place JOINT SEALING TAPE. Then, apply one more coat of the waterproofing slurry to cover the tape.

After the waterproofing slurry has hardened, tiles are fixed using high-performance adhesives such as ISOMAT AK-20, ISOMAT AK-22, ISOMAT AK-25, or ISOMAT AK-ELASTIC.

Packaging

Rolls of 12 cm x 50 m and 12 cm x 10 m.

Storage

Stored in original, unopened packaging, in places protected from moisture and frost.

ISOMAT S.A.
BUILDING CHEMICALS, MORTARS & PAINTS
HEADQUARTERS – THESSALONIKI, GREECE
17th km Thessaloniki – Ag. Athanasios Road
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece
T +30 2310 576000
www.isomat.eu e-mail: support@isomat.eu