

# SM-27

## Special solvent for epoxy coatings

### Description

SM-27 is an aromatic hydrocarbon used in combination with epoxy coatings.

### Fields of application

Specifically designed for thinning EPOXYCOAT and EPOXYCOAT-S epoxy coatings. Suitable also for thinning polyurethane-based products (paints, liquid waterproofing membranes, etc.). Also effective for cleaning application tools.

### Technical data

Color: clear / colorless  
Density: 0.86 ± 0.02 kg/l

### Directions for use

SM-27 is used for thinning epoxy materials at a ratio of up to 20% by weight.

### Consumption

Consumption varies depending on the nature of the application.

### Packaging

0.75 l & 4 l containers.

### Shelf life – Storage

12 months from production date, in original, sealed containers, stored at temperatures above 5°C and protected from high temperatures (<+30°C).

### Remarks

- Ensure adequate ventilation when applying SM-27 indoors.
- Keep away from sources of ignition during application – No smoking.
- Please consult the safety instructions written on the packaging before use.
- For further information, please refer to the Material Safety Data Sheet.

#### ISOMAT S.A.

BUILDING CHEMICALS AND MORTARS

#### MAIN OFFICES - FACTORY:

17<sup>th</sup> km Thessaloniki - Ag. Athanasios Road,  
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece,  
Tel.: +30 2310 576 000, Fax: +30 2310 722 475

[www.isomat.eu](http://www.isomat.eu) e-mail: [support@isomat.eu](mailto:support@isomat.eu)